

Marine transport IMDG

MARINE POLLUTANT

Transport as limited quantities according to 3.4 IMDG Code is possible.

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultant Lutz Harder GmbH)

SECTION 15: Additional Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC Standard

VOC Content	0%
VOC Value	None

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other Information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed. For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.


The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU- directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H261 In contact with water releases flammable gases.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

Issued By: York Survey Supply Centre Ltd

Follow us!



Prospect House, George Cayley Drive, Clifton Moor, York, England YO30 4XE

Tel: +44 (0) 1904 692723 Fax: +44 (0) 1904 690385
E-Mail: sales@yorksurvey.co.uk www.yorksurvey.co.uk



Paint-Mark

Code: 16401 - 16408
white-yellow-red-blue-green-orange-black

Health & Safety Data Sheet

According to Regulation (EU) No 830/2015 and Regulation (EC) No 1272/2008

YSSC Paint-Mark (750ml)

Revision Date: 10/12/2020 / Version: 3

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

Trade Name: YSSC Paint-Mark

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: Industrial applications, for use by hand or suitable applicator.

1.3. Details of the supplier of the safety data sheet

Company Name: York Survey Supply Centre Ltd

Company Address: Prospect House, George Cayley Drive, Clifton Moor, York, YO30 4XE

Tel: +44 (0) 1904 692723

E-mail: sales@YorkSurvey.co.uk

Web: www.YorkSurvey.co.uk

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

Hazard classes and Hazard categories	Hazard Statements
Aerosol 1	H222, H229
Aquatic Chronic 2	H411

2.2. Label elements Hazard pictograms:

Hazard pictograms:



Signal word: Danger

Hazard statements:

- H222 Extremely flammable aerosol.
- H229 Pressurised container: May burst if heated.
- H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards Results of PBT and vPvB assessment:

Product has an anesthetic effect.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

! Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / Information On Ingredients

Description

Line Marker based on synthetic resin binder, solvent and pigments.

3.1. Substances N/A

3.2. Mixtures Description: Hazardous Ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
8050-31-5	232- 482-5	Resin acids and rosin acids, esters with glycerol	10<15	R43 Xi; R36/38 N; R51/53
NA	NA	Pigment	12< 18	No Classified
115-10-6	204-065-8	Dimethyl ether	30< 34	Flam. Gas 1, H220 / Press. Gas, H280
471-34-1	207-439-9	Calcium carbonate	18 < 21	No Classified
109-87-5	203-714-2	Dimethoxymethane	8< 12	Flam. Liq. 3, H226 / STOT SE 3, H336

SECTION 4: First Aid Measures

4.1. Description of first aid measures

General information:

Remove contaminated soaked clothing immediately.

Inhalation:

Remove the casualty into fresh air and keep him immobile.
 In the event of symptoms refer for medical treatment.

Skin Problem:

In case of contact with skin wash off with soap and water.
 Consult a doctor if skin irritation persists.

Eye:

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Ingestion:

Do not induce vomiting.

SECTION 12: Ecological Information

12.1. Toxicity

No information available.

12.2. Persistence and degradability: No information available.

12.3. Bioaccumulative potential: No information available.

12.4. Mobility in soil: No information available.

12.5. Results of PBT and vPvB assessment: The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects: No known significant effects or critical hazards

Toxic to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Waste Code Number	Name of Waste
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

SECTION 14: Transport Information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number:	1950	1950	
14.2. UN proper shipping name:	AEROSOLS	AEROSOLS (ZINC POWDER)	Aerosols, flammable
14.3. Transport hazard class(es):	2.1	2.1	2.1
14.4. Packing group:	-	-	-
14.5. Environmental hazards:	Yes	Yes	Yes
14.6. Special precautions for user	No information available		

14.7. Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code:

Not applicable

Land and inland navigation transport ADR/RID

Hazard label(s) 2.1
 Tunnel restriction code D
 Classification code 5F
 transport in "limited quantities" according to 3.4 ADR is possible

Relative density: Not determined
Vapour density: Not determined
Solubility in water: Not determined
Solubility/other: Not determined
Partition coefficient n- octanol/water (log P O/W): Not determined
Decomposition temperature: Not determined
Viscosity dynamic: Not determined
Viscosity kinematic: Not determined
Oxidising properties: Not determined

No information available.

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

9.2. Other information: No further relevant information available

SECTION 10: Stability and Reactivity

- 10.1. Reactivity:** No
10.2. Chemical stability: No further relevant information available
10.3. Possibility of hazardous reactions: Possibility of hazardous reaction
10.4. Conditions to avoid: Keep away from heat. Formation of explosive gas/air mixtures.
10.5. Incompatible materials: No further relevant information available
10.6. Hazardous decomposition products: No further relevant information available
Thermal decomposition: No decomposition if used as directed.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute toxicity

	Value/Validation	Species	Method	Remark
LD50 acute oral	>2000 mg/kg	Rat		Information concerns to main component.
LD50 acute dermal	1100 mg/kg			Xylene
LC50 acute inhalation	> 5 mg/l (4 h)	Rat		Aluminium
Irritability skin	irritant			
Irritability eye	irritant			

Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation. Irritates respiratory tract.
 Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals. Other hazardous properties may not be excluded.

Medical treatment.

4.2. Most important symptoms and effects, both acute and delayed:

No further relevant information available.

4.3. Indication of any immediate medical attention and special treatment needed:

No information available.

SECTION 5: Firefighting Measures

5.1. Extinguishing media

Suitable: Alcohol-resistant foam, Carbon dioxide, Dry sand

Unsuitable: Water

5.2. Special hazards arising from the substance or mixture: May lead to formation of explosive/easily ignitable vapour air mixtures. Danger of bursting.

5.3. Advice for fire-fighters: Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional Information: Vapours are heavier than air and will spread on the ground. Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions:

Ensure adequate ventilation.

Use personal protective clothing. Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

Advice for emergency responders:

Use personal protective equipment

6.2. Environmental protection measures

Inform pollution control authorities if product gets into the sewerage systems or open waters. Do not discharge into the drains or bodies of water.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

6.4. Reference to other sections:

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Advice on Safety Handling:

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace. Take measures against electrostatically charging.

General protective measures:

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs. Wash hands before breaks and after work.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material. Pressurized container.

Do not pierce or burn even after use.

Vapours can form an explosive mixture with air. Avoid effect of heat.

Use explosion-proof equipment / fittings and non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F). Store container at cool and aired place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

SECTION 8: Exposure Controls / Personal Protection

8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
115-10-6	Dimethyl ether	8 hours	1920	N/A	IOELV
109-87-5	Dimethoxymethane	8 hours Short-term	3110	1000	EH40/2005

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
115-10-6	Dimethyl ether	8 hours	1920	N/A	Skin Eye
109-87-5	Dimethoxymethane	8 hours Short-term	3110	1000	Skin Eye

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

Hand protection

It is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

Eye protection

Tightly fitting goggles

Other protection measures

Protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance: Aerosol

Odour: Solvent-like

Colour: Various

pH (20°C): Not determined

Boiling Point: Not Applicable

Melting point / Freezing point: not determined

Flash point: Not applicable (Aerosol)

Vapourisation rate: Not determined

Flammable (solid): Not determined

Flammability (gas): Not determined

Ignition temperature: Not determined

Self ignition temperature: Not determined

Lower explosion limit: Not determined

Upper explosion limit: Not determined

Vapour pressure: Not determined