

### 13. DISPOSAL CONSIDERATIONS

WASTE FROM RESIDUES/UNUSED PRODUCTS: Do not allow to enter drains or watercourses or dispose of where ground or surface waters may be affected.

#### CONTAMINATED PACKAGING:

Wastes, including emptied aerosols, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act. Using the information provided in this safety data sheet, advice should be obtained from the relevant environment agency whether the special waste regulations apply.

### 14. TRANSPORT INFORMATION

UN NUMBER: UN1950  
SHIPPING NAME: Aerosols  
HAZARD CLASS: 2.1 (For Sea Transport). Classification code 5f  
EmS: F-D, S-U  
CLASS (LQ): 2  
LABELLING: 2.1

### 15. REGULATORY INFORMATION

#### SYMBOLS:



Extremely Flammable



Irritant

R-PHRASE(S): R12 Extremely flammable  
R36 Irritating to eyes  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment  
R66 Repeated exposure may cause skin dryness or cracking  
R67 Vapours may cause drowsiness and dizziness

S-PHRASE(S): S2 Keep out of the reach of children  
S9 Keep container in a well ventilated place  
S16 Keep away from sources of ignition - no smoking  
S23 Do not breathe gas/fumes/vapour/spray  
S29/35 Do not empty into drains; dispose of this material and its container in a safe way  
S36 Wear suitable protective clothing  
S46 If swallowed, seek medical advice immediately and show this container or label  
S51 Use only in well ventilated areas

No chemical safety assessments have been carried out for any of the substances used in this preparation.

### 16. OTHER INFORMATION

#### USES ADVISED AGAINST:

The product should not be used for any purposes other than its intended use.  
Handling, storage and conditions to avoid instructions must be followed at all times.

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemical (Hazard Information and Packaging) Regulations. The information we have provided is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. The information relates only to the material designated and may not be valid for such material used in combination any other materials unless specified in the text.



#### Follow us!

York Survey Supply Centre  
@York\_Survey  
@York\_Survey

Prospect House, George Cayley Drive, Clifton Moor, York, England YO30 4XE

Tel: +44 (0) 1904 692723 Fax: +44 (0) 1904 690385  
E-Mail: sales@yorksurvey.co.uk www.yorksurvey.co.uk

# YORK Survey Supply

## LineMarker

white-yellow-red-blue-green-orange-black



Code: 16751 - 16758

## Health & Safety Data Sheet

# Product Safety Data Sheet

## LineMarker

white - yellow - red - blue - green - orange - black

EU regulation 1907/2006/EEC - (REACH)

### 1. IDENTIFICATION OF SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

PRODUCT NAME: LINEMARKER  
USE: Open system operated by non-trained consumer.  
APPLICATION/CONDITIONS: Linemarking Spray Paint.  
SUPPLIER: YORK SURVEY SUPPLY CENTRE LTD.  
Prospect House, George Cayley Drive, Clifton Moor, York, YO30 4XE : United Kingdom

### 2. HAZARDS IDENTIFICATION

MOST IMPORTANT HAZARDS: Harmful to aquatic environment. Vapours may cause drowsiness and dizziness. Extremely flammable.  
SPECIFIC HAZARDS: Irritating to eyes. Repeated exposure may cause skin dryness and cracking.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

IDENTIFICATION OF THE PREPARATION: A mixture of resins, pigments, mineral extenders, additives, organic solvents and organic gases.

CHEMICAL NAME	CAS-No	EC-No	CLASS	WEIGHT	REGISTRATION-No
Mixed Aromatic Hydrocarbons	64742-95-6	649-356-00-4	R10 Xn; R37 R65 R66 R67 N; R51/53	10-15%	-
2-Butoxyethanol	111-76-2	603-014-00-0	Xn; R20/21/22 Xi; R36/38	5-10%	-
1-Methoxy-2-Propanol	107-98-2	603-064-00-3	R10	5-10%	-
Propan-2-one	67-64-1	200-662-2	R11, R36, R66, R67	40-60%	-
Butane	106-97-8	203-448-7	F+; R12	10-30%	-
Propane	74-98-6	200-827-9	F+; R12	10-30%	-

VOC Content - 55g/L - 58g/L  
Contains no known PBTs or vPvBs

### 4. FIRST AID MEASURES

GENERAL ADVICE: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.  
INHALATION: Remove to fresh air, keep the patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.  
SKIN CONTACT: Remove contaminated clothing immediately and wash affected skin with soap and water. DO NOT use solvents or thinners as skin cleaning agents.  
EYE CONTACT: Contact lenses should be removed. Promptly wash eyes with lots of water while lifting the eyelids. Continue to rinse for at least 15 minutes and get medical attention.  
INGESTION: If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting.

### 5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Recommended use: Alcohol resistant foam, carbon dioxide (CO<sub>2</sub>), dry powder, water spray. Do not use water jet. Cool containers with spray water.  
EXTINGUISHING MEDIA WHICH MUST NOT BE USED FOR SAFETY REASONS: Do NOT use high pressure inert gas or water jets.  
SPECIFIC HAZARDS: Fire may produce dense black smoke containing hazardous combustion products (see heading 10). Decomposition products may be a hazard to health. Do not allow run-off from fire fighting to enter drains or watercourses.

### SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS:

In the event of fire, wear self-contained breathing apparatus.

### 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Remove all sources of ignition. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing vapours. Refer to protective measures listed in sections 7 and 8.  
ENVIRONMENTAL PRECAUTIONS: DO NOT allow to enter drains or watercourses. If the product enters drains or sewers, the local water company should be informed immediately. In the case of contamination of streams, rivers or lakes, inform the relevant environment Agency. Vapours are heavier than air and may spread along floors. Vapours may form an explosive mixture with air.  
METHODS FOR CLEANING UP: Contain and collect spillage with non-combustible absorbent materials, (e.g. sand, earth, vermiculite, diatomaceous earth) and place in a suitable container for disposal in accordance with the waste regulations (see section 13). Clean the spill area, preferably with a detergent. Avoid the use of solvents.

### 7. HANDLING AND STORAGE

HANDLING: Keep the aerosol in a cool, dry place. Exclude sources of heat, sparks and open flame. Do not use sparking tools around aerosols. Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. For personal protection, see section 8. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits. Never apply pressure to the aerosol, the aerosol is a pressurised object and may explode

if pressure is applied.

GENERAL: The accumulation of vapours in an enclosed area may result in spontaneous combustion, use only in well ventilated areas. Use responsibly and in the correct manner. Wear the appropriate personal protective equipment, as outlined in section 8.  
STORAGE: Observe the label precautions. Store between 5 and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CHEMICAL NAME	8hr TWA <sup>(1)</sup>	15min <sup>(2)</sup>	Type <sup>(4)(3)</sup>	Ref
Mixed Aromatic Hydrocarbons	25ppm 50mgm <sup>-3</sup>		Rec	SUP
2-Butoxyethanol	25ppm	50ppm	WEL Sk Bmgv	EH40
1-Methoxy-2-Propanol	100ppm 375mgm <sup>-3</sup>	150ppm 560mgm <sup>-3</sup>	WEL Sk	EH40

Propan-2-one  
(1) Long term exposure limits - 8hr time weighted average (2) Short term exposure limit - 15 minute reference period  
(3) "Sk" indicates a risk of absorption through the skin. "Bmgv" indicates a biological monitoring guidance value.  
(4) "WEL" indicates a Workplace Exposure Limit. WELs are taken from the current version of EH40 except those marked "SUP" which are assigned by the supplier of the substance.

ENGINEERING MEASURES: Provide adequate ventilation. All PPE used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH regulations.

### PERSONAL PROTECTION EQUIPMENT:

RESPIRATORY PROTECTION: If exposure to hazardous substances identified cannot be controlled by the provision of local exhaust ventilation and good general extraction, suitable respiratory protective equipment should be worn.

### HAND PROTECTION:

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Barrier creams may help to protect exposed areas of skin, but are not substitutes for full physical protection. They should not be applied once exposure has occurred. Eye protection designed to protect against liquid splashes should be worn. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

### EYE PROTECTION:

### SKIN & BODY PROTECTION:

### 9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Aerosol  
FLASHPOINT: Not known for blend  
COLOUR: Various  
ODOUR: Aromatic

### 10. STABILITY AND REACTIVITY

STABILITY: Stable under the recommended storage and handling conditions (see section 7).  
CONDITIONS TO AVOID: Applying heat or pressure to the aerosol may result in explosion and fire. Naked flames, smoking, wet and damp storage conditions and mishandling may also result in explosion and fire.

### MATERIALS TO AVOID:

Keep away from oxidising agents, strongly alkaline and strongly acidic materials in order to avoid exothermic reactions.  
HAZARDOUS DECOMPOSITION PRODUCTS: In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

### 11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: Splashes in the eye may cause irritation and reversible local damage.  
LOCAL EFFECTS: Repeated or prolonged contact with the product may lead to removal of natural fats from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous systems. Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

### SENSITIZATION:

CHRONIC TOXICITY:  
LONG TERM TOXICITY:

Contains no known category 1 or 2 carcinogens, mutagens or reproductive toxicants.

### 12. ECOLOGICAL INFORMATION

MOBILITY:  
PERSISTENCE AND DEGRADABILITY:  
BIOACCUMULATION:  
ECOTOXICITY EFFECTS: No data is available on the product itself. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
This product should not be allowed to enter drains or watercourses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

### ENDOCRINE DISRUPTING POTENTIAL:

Contains no known substances that require a chemical safety report.

(continued overleaf)